

# Magnetic drilling machine

# ECO.40S

## Technical data

	Metric	Imperial
Annular cutting	Ø 12 - 40 mm	Ø 1/2" - 1 9/16"
Twist drilling	Ø 1 - 16 mm	Ø 1/16" - 5/8"
Countersinking	Ø 10 - 45 mm	Ø 3/8" - 1 3/4"
Length	264 mm	10 3/8"
Width	180 mm	7 1/16"
Height	360 - 440 mm	14 3/16" - 17 5/16"
Stroke	145 mm	5 11/16"
Weight	11,2 kg	24.7 lbs
Magnet (l x w x h)	160 x 80 x 42 mm	6 5/16" x 3 1/8" x 1 5/8"
Magnetic force	1500 kg	3305 lbs
Motor power	1150 W	10.5 A
Total power	1200 W	10.9 A
Speed (no load)	600 rpm	
Speed (load 1150 W, 10.5 A)	380 rpm	
Spindle (Weldon)	19,05 mm	3/4"
Voltage	110 - 120 V / 60 Hz	
	220 - 240 V / 50 - 60 Hz	



## Features:



Oil lubricated  
gearbox



Magnet  
LED-indicator

## Benefits:

- Lightest 40 mm (1 9/16") magnetic drilling machine;
- Fits cutters up to 110 mm (4 5/16") in length;
- High Efficiency motor with less heat generation;
- High accuracy capstan hub;
- Direct spindle drive and integrated tool cooling and lubrication;
- Integrated slide and one-speed oil lubricated gearbox for:
  - High accuracy;
  - Enlarged lifecycle;
  - Minimal vibration;
- High precision height adjustment for:
  - Low maintenance;
  - Minimal wear correction;
- Strong dual coil CNC machined magnet.